



TECHNICAL DATA

Black Back Banner 300g 500D*500D 9*9



Item	Data	Unit	Method
Yarn	500x500	Denier	DIN60001
Net structure	9x9	Thread / Inch	DIN53853
Net weight	45	g/sq.m	DIN53352
PVC film weight	255±10	g/sq.m	DIN53352
Product weight	300±10	g/sq.m	DIN53352
Thickness		mm	DIN53353
Products width	0.914-5.00	m	—
Tearing strength (L*W)	50x60	N/5cm	DIN53363
Tensile strength (L*W)	780x780	N/5cm	DIN53354
Elongation value (L*W)		%	DIN53354
Peeling strength	30x30	N/5cm	DIN53357
Color fastness	5	Level	ASTM D 1003
Temperature	-20~+60	°C	DIN53372
Expired time	6-12months		—
Flame retardant	pass		DIN75200
Anti-wicking	without		—
Anti-frost	without		—
Anti-mildew	without		—
Acrylic lacquer	without		—
Applications	JANEHONG Flex Banner 300g 500D*500D 9*9 are mainly for outdoor signs usage, include Event flags, Banner displays, P.O.P signs and others. Its excellent printability allows a very clear and vivid image on the billboard. It is featured by its high physical performance in peel, tensile and tear strength. This high quality front-lit flex even can be used in extreme cold/hot or windy outdoor conditions. It optimized for Solvent, Eco-solvent, UV curable inkjet printer, such as VUTEK, NUR, HP SCITEX, EPSON, DGI, ROLAND, MUTOH, MIMAKI, ARIZONA, SALASA, TECKWIN, FLORA, INFINITI, etc		

Durability

Durability is based on field experience and exposure tests in China. Outdoor durability is 1 year when properly processed and applied (unprinted film vertical exposure).

Shelf Life

Shelf life is 1 year from factory shipment.

Storage Condition

Free from excessive moisture, temperature, direct sunlight (20°C x 50% R.H.).