



Shanghai JaneHong New Material Technology Co., Ltd.

Tel: 0086 21 63636387

Fax: 0086 21 52844402

## TECHNICAL DATA

### Banner 13oz 1000D\*1000D 9\*9



Item	Data		Unit	Method
Yarn	1000 x 1000		Denier	DIN60001
Net structure	9x9		Thread / Inch	DIN53853
Net weight	80		g/sq.m	DIN53352
PVC film weight	360		g/sq.m	DIN53352
Product weight	440 ( $\pm 10$ )		g/sq.m	DIN53352
Thickness	0.36 ( $\pm 0.02$ )		mm	DIN53353
Products width	0.914 ~ 5.00		m	~~~
Tearing strength	L	270	N/5cm	DIN53363
	W	270		
Tensile strength	L	1350	N/5cm	DIN53354
	W	1350		
Elongation Value	L	15	%	DIN53354
	W	16		
Peeling Strength	36		N/5cm	DIN53357
Lighting Transmission	15		%	ASTM D 1003
Temperature	-30°C ~ +70°C		°C	DIN53372
Expired time	6 ~ 12 months			~~~
Flame retardant	pass			DIN75200
Anti-wicking	without			~~~
Anti-frost	without			~~~
Anti-mildew	without			~~~
Acrylic lacquer	without			~~~
Applications	JANEHONG Banner 13oz 1000D*1000D 9*9 are mainly for outdoor signs usage, include Event flags, Banner displays, P.O.P signs and others. Its excellent printability allows a very clear and vivid image on the billboard. It is featured by its high physical performance in peel, tensile and tear strength. The light weigh and economical cost make it more popular for use.			
	It optimized for Solvent, Eco-solvent, UV curable inkjet printer, such as VUTEK, NUR, HP SCITEX, EPSON, DGI, ROLAND, MUTOH, MIMAKI, ARIZONA, SALASA, TECKWIN, FLORA, INFINITI, etc			

### Durability

Durability is based on field experience and exposure tests in China. Outdoor durability is 1 year when properly processed and applied (unprinted film vertical exposure).

### Shelf Life

Shelf life is 1 year from factory shipment.

### Storage Condition

Free from excessive moisture, temperature, direct sunlight (20°C x 50% R.H.).